

## I CLAIM

1. A method of increasing air temperature of compressed air flowing to an air drying device through an air delivery inlet duct from an air compressor comprising:

compressing ambient air with said air compressor,

directing compressed air from said air compressor as a compressed air flow toward said air delivery inlet duct,

diverting a portion of said compressed air flow from said air delivery inlet duct back to said air compressor to raise the temperature of said compressed air flow, and

passing said compressed air flow from said air delivery inlet duct to said air drying device.

2. A method according to Claim 1 further comprising varying the portion of said compressed air flow diverted from said air delivery inlet duct.

3. A method according to Claim 1 further comprising diverting between about one percent and about eighty percent of total air compressed by said compressor back to said compressor.

4. A method according to Claim 1 further comprising varying the portion of said compressed air flow diverted from said air delivery inlet duct and maintaining a selected elevated air temperature of compressed air passed to said air drying device.

5. A method according to Claim 1 further comprising compressing air in said compressor to between about 0.5 to about 10.0 pounds per square inch above

ambient pressure.

drawing ambient air into said air compressor,

recirculating a portion of said compressed air flow back to said

directing the remaining portion of said compressed air flow to

7. A method according to Claim 6 further comprising compressing air in said compressor to a pressure of between about 0.5 to about 10.0 pounds per square inch above ambient air pressure.

9. A method according to Claim 6 further comprising maintaining a predetermined elevation in compressed air temperature directed to said air delivery device above ambient air temperature.

improvement comprising a compressed air recirculation loop leading from said air delivery inlet duct back to said air compressor and a valve for diverting a portion of air flowing from said compressor toward said air delivery inlet duct back to said air compressor through said recirculation loop.

11. An air blower system according to Claim 10 wherein said air compressor is a single stage centrifugal blower.

12. An air blower system according to Claim 10 wherein said valve is an adjustable valve.